Lighting Fixture Schedule

KBD - Building 1315

Prepared By: Mike Roberts

Type	Description	Manufacturer		Lamp				Ballast	Input Watts	Remarks
		Name	Catalog No.	Qty.	Mfgr.	Type	K			
A2	SPECIFICATION GRADE 2'X4' RECESSED GRID TROFFER, FLUSH STEEL DOOR FRAME, CAM LATCHED & HINGED, PATTERN 12 ACRYLIC LENS, .125 THICKNESS, PROGRAM START ELECTRONIC BALLAST, INTEGRAL T-BAR CLIPS	COLUMBIA	ST824-232G-FSA12.125-EPU-F0835-C388-RCW	2	Sylvania Philips GE	FO32T8 32 WATT	4100	Program Start Electronic Ballast	56	
A2X	SPECIFICATION GRADE 2'X4' RECESSED GRID TROFFER, FLUSH STEEL DOOR FRAME, CAM LATCHED & HINGED, PATTERN 12 ACRYLIC LENS, .125 THICKNESS, PROGRAM START ELECTRONIC BALLAST, INTEGRAL T-BAR CLIPS, SELF TEST EMERGENCY BATTERY PACK	COLUMBIA	ST824-232G-FSA12.125-EPU-F0835-C468-EL(B50ST)-RCW	2	Sylvania Philips GE	FO32T8 32 WATT	4100	Program Start Electronic Ballast	56	Provide factory Installed Bodine B50ST self test Emergency Battery Pack
A3	SPECIFICATION GRADE 2'X4' RECESSED GRID TROFFER, FLUSH STEEL DOOR FRAME, CAM LATCHED & HINGED, PATTERN 12 ACRYLIC LENS, .125 THICKNESS, PROGRAM START ELECTRONIC BALLAST, INTEGRAL T-BAR CLIPS	COLUMBIA	ST824-332G-FSA12.125-3EPU-F0835-C388-RCW	3	Sylvania Philips GE	FO32T8 32 WATT	4100	Program Start Electronic Ballast	87	
A5	SPECIFICATION GRADE 2'X4' RECESSED GRID TROFFER, FLUSH STEEL DOOR FRAME, CAM LATCHED & HINGED, PATTERN 12 ACRYLIC LENS, .125 THICKNESS INVERTED, PROGRAM START ELECTRONIC BALLAST, INTEGRAL T-BAR CLIPS, TRIPLE GASKETING	COLUMBIA	ST824-232G-FSA12.125INV-EPU-F0835-C388-G3-RCW	2	Sylvania Philips GE	FO32T8 32 WATT	4100	Program Start Electronic Ballast	58	
A8	SPECIFICATION GRADE 2'X4' RECESSED GRID TROFFER, FLUSH STEEL DOOR FRAME, CAM LATCHED & HINGED, PATTERN 12 ACRYLIC LENS, .125 THICKNESS INVERTED, PROGRAM START ELECTRONIC BALLAST, INTEGRAL T-BAR CLIPS, TRIPLE GASKETING	COLUMBIA	ST824-332G-FSA12.125INV-3EPU-F0835-C388-G3-RCW	3	Sylvania Philips GE	FO32T8 32 WATT	4100	Program Start Electronic Ballast	87	
C1	SPECIFICATION GRADE 2'X4' SURFACE TROFFER, FLUSH STEEL DOOR FRAME, CAM LATCHED & HINGED, PATTERN 12 ACRYLIC LENS, .125 THICKNESS INVERTED, PROGRAM START ELECTRONIC BALLAST, TRIPLE GASKETING	COLUMBIA	PM24-332F-FSA12.125INV-3EPU-F0835-C388-G3-RCW	3	Sylvania Philips GE	FO32T8 32 WATT	4100	Program Start Electronic Ballast	87	
E2	4' X 4' INDUSTRIAL STRIP, 22GA CHANNEL HOUSING, PROGRAM START ELECTRONIC BALLAST, WIRE GUARD, CHAIN HANGER KIT WHERE REQUIRED, BAKED WHITE ENAMEL FINISH	COLUMBIA	CS4-232-EPU-CSWG4-CSHC-RCW	2	Sylvania Philips GE	FO32T8 32 WATT	4100	Program Start Electronic Ballast	58	
F1	6" RECESSED DOWNLIGHT ONE-PIECE 22GA NON-CORROSIVE STEEL HOUSING, PRE-WIRED SNAP COVER J-BOX, HIGH PURITY ALUMINUM ALZAK SEMI-DIFFUSED REFLECTOR, PHILIPS FORTIMO DLM LED MODULE, 24" FLAT BAR HANGAR, STANDARD 0-10V DIMMING	PRESCOLITE	LF6LED-LF6LED7-35K-WT-B24-RCW	N/A	N/A	LED	4000	Electronic Driver	36	
F1D	6" RECESSED DOWNLIGHT ONE-PIECE 22GA NON-CORROSIVE STEEL HOUSING, PRE-WIRED SNAP COVER J-BOX, HIGH PURITY ALUMINUM ALZAK SEMI-DIFFUSED REFLECTOR, PHILIPS FORTIMO DLM LED MODULE, 24" FLAT BAR HANGAR, STANDARD 0-10V DIMMING	PRESCOLITE	LF6LED-LF6LED7-35K-WT-B24-RCW	N/A	N/A	LED	4000	Electronic 0-10 Volt Dimming Driver	36	
H1	4'X4' UNDER CABINET TASK LIGHTING FIXTURE, PROGRAMMED START ELECTRONIC BALLAST, PREMIUM WHITE ACRYLIC DIFFUSER, BAKED WHITE ENAMEL FINISH, PAINTED AFTER FABRICATION	COLUMBIA	UC48-132-EPU-RCW	1	Sylvania Philips GE	FO32T8 32 WATT	4100	Program Start Electronic Ballast	33	
P1	10" X 8' HIGH PERFORMANCE PENDANT LINEAR INDIRECT/DIRECT FIXTURE, RECTANGULAR HOUSING, EXTRUDED ACRYLIC SOFT GLOW LENS, ELECTRONIC PROGRAM START BALLAST, 90% MINIMUM EFFICIENCY, STANDARD FINISH SELECTED BY ARCHITECT, DUST COVER	LITE CONTROL	P-ID-61-4-8-TB-SGL-CXS-LP/ELB-1CWQ-LK-SP-UNV-RCW	4	Sylvania Philips GE	FO32T8 32 WATT	4100	Program Start Electronic Ballast	109	
P1D	10" X 8' HIGH PERFORMANCE PENDANT LINEAR INDIRECT/DIRECT FIXTURE, RECTANGULAR HOUSING, EXTRUDED ACRYLIC SOFT GLOW LENS, ELECTRONIC 0-10V DIMMING BALLAST, 90% MINIMUM EFFICIENCY, STANDARD FINISH SELECTED BY ARCHITECT, DUST COVER	LITE CONTROL	P-ID-61-4-8-TB-SGL-CXS-LPD/ELB-1CWQ-CS/DLH-LK-SP-UNV-RCW	4	Sylvania Philips GE	FO32T8 32 WATT	4100	Electronic Dimming Ballast	109	Provide factory Installed Integral photocell where indicated on drawings
P1DX	10" X 8' HIGH PERFORMANCE PENDANT LINEAR INDIRECT/DIRECT FIXTURE, RECTANGULAR HOUSING, EXTRUDED ACRYLIC SOFT GLOW LENS, ELECTRONIC 0-10V DIMMING BALLAST, 90% MINIMUM EFFICIENCY, STANDARD FINISH SELECTED BY ARCHITECT, DUST COVER, INTEGRAL EMERGENCY BATTERY PACK	LITE CONTROL	P-ID-61-4-8-TB-SGL-CXS-LPD/ELB-1CWQ-CS/DLH-LP/EF-LK-SP-UNV-RCW	4	Sylvania Philips GE	FO32T8 32 WATT	3500	Electronic Dimming Ballast	109	Provide factory Installed Integral P-Cell & EM Pack where indicated on drawings
P1X	10" X 8' HIGH PERFORMANCE PENDANT LINEAR INDIRECT/DIRECT FIXTURE, RECTANGULAR HOUSING, EXTRUDED ACRYLIC SOFT GLOW LENS, ELECTRONIC PROGRAM START BALLAST, 90% MINIMUM EFFICIENCY, STANDARD FINISH SELECTED BY ARCHITECT, DUST COVER, INTEGRAL EMERGENCY BATTERY PACK	LITE CONTROL	P-ID-61-4-8-TB-SGL-CXS-LP/ELB-1CWQ-LP/EF-LK-SP-UNV-RCW	4	Sylvania Philips GE	FO32T8 32 WATT	3500	Program Start Electronic Ballast	109	Provide factory Installed Bodine LP600STU Self Test Emergency Battery Pack
P2	10" X 4' HIGH PERFORMANCE PENDANT LINEAR INDIRECT/DIRECT FIXTURE, RECTANGULAR HOUSING, EXTRUDED ACRYLIC SOFT GLOW LENS, ELECTRONIC PROGRAM START BALLAST, 90% MINIMUM EFFICIENCY, STANDARD FINISH SELECTED BY ARCHITECT,DUST COVER	LITE CONTROL	P-ID-61-2-4-TB-SGL-CXS-LP/ELB-1CWQ-LK-SP-UNV-RCW	2	Sylvania Philips GE	FO32T8 32 WATT	3500	Program Start Electronic Ballast	58	
S1	6" SEALED RECESSED DOWNLIGHT ONE-PIECE 22GA NON-CORROSIVE STEEL HOUSING, PRE-WIRED SNAP COVER J-BOX, HIGH PURITY ALUMINUM ALZAK REFLECTOR, PHILIPS GEN 3 FORTIMO DLM LED MODULE, 27" FLAT BAR HANGAR, STANDARD 0-10V DIMMING	PATHWAY	6VLED-2000-35K-120/277V-WL-27BH-6VLEDFRPWL-RCW	N/A	N/A	LED	4000	Electronic Driver	32	
W1	5" X 7" X 4' WALL MOUNT BATHROOM MIRROR FIXTURE, ONE PIECE CLEAR ACRYLIC DIFFUSER, UPLIGHT,DOWNLIGHT, FRONTLIGHT, PROGRAM START ELECTRONIC BALLAST, HEAVY GUAGE STEEL HOUSING, BAKED WHITE ENAMEL FINISH	COLUMBIA	SA4-132-EPU-LSW-LCO-RCW	1	Sylvania Philips GE	FO32T8 32 WATT	3500	Program Start Electronic Ballast	33	
X1	LED UNIVERSAL MOUNT SINGLE FACE EXIT SIGN WITH HIGH STRENGTH CAST ALUMINUM HOUSING AND FACE PLATE, PROVIDE WITH POLYCARBONATE FACE SHIELD, TAMPER-RESISTANT SCREWS, FACING AND ARROWS AS REQUIRED	DUAL-LITE	SESXW-VTR-RCW	N/A	N/A	LED	N/A	N/A	3	Verify Lens Color Prior To Ordering
X2	LED UNIVERSAL MOUNT DOUBLE FACE EXIT SIGN WITH HIGH STRENGTH CAST ALUMINUM HOUSING AND FACE PLATE, PROVIDE WITH POLYCARBONATE FACE SHIELD, TAMPER-RESISTANT SCREWS, FACING AND ARROWS AS REQUIRED	DUAL-LITE	SEDXW-VTR-RCW	N/A	N/A	LED	N/A	N/A	3	Verify Lens Color Prior To Ordering
O/S-C	CEILING MOUNTED DUAL TECHNOLOGY MOTION SENSOR CONSTRUCTED OF HIGH-IMPACT INJECTED MOLDED PLASTIC, WITH DIGITAL ARCHITECTURE USING TWO ULTRASONIC TRANSMITTERS AND TWO NARROW BANDWIDTH RECEIVERS, THE SENSOR WILL OPERATE IN HIGH SENSITIVITY AND MISER MODES, SELF ADJUST ULTRASONIC AND INFRARED SENSITIVITY TIMER, AND AIR CURRENT COMPENSATION, PROVIDE VISUAL STATUS REPORTING, WITH RELAY & PHOTOCELL	COOPER CONTROLS	OAC-DT-1000-R	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
O/S-S	WALL SWITCH MOUNTED DUAL TECHNOLOGY MOTION SENSOR CONSTRUCTED OF HIGH-IMPACT INJECTED MOLDED PLASTIC, WITH DIGITAL ARCHITECTURE USING TWO ULTRASONIC TRANSMITTERS AND TWO NARROW BANDWIDTH RECEIVERS, THE SENSOR WILL OPERATE IN HIGH SENSITIVITY AND MISER MODES, SELF ADJUST ULTRASONIC AND INFRARED SENSITIVITY, TIMER, AND AIR CURRENT COMPENSATION, PROVIDE VISUAL STATUS REPORTING, WITH RELAY PHOTOCELL, ISOLATED FORM-C RELAY FOR HVAC CONTROL, METAL MOUNTING TABS	COOPER CONTROLS	ONW-D-1001-SP	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
PHOTO CELL	DAY-LIGHTING CEILING MOUNTED PHOTOCELL	COOPER CONTROLS	DLC-PD-DIM	N/A	N/A	N/A	N/A	N/A	N/A	
AA	WALL MOUNTED SIGN LIGHT FIXTURE WITH 12" ARM, EXTRUDED ALUMINUM FIXTURE HOUSING INTEGRAL ELECTRONIC LED DRIVER AND LINE VOLTAGE POWER SUPPLY	LUMENPULSE	LOGHO-120-24-35K-30X60-WAM12-FINISH-NO-CRC-RCW	INCL	INCL	LED	3500	Electronic Driver	31	
BB	BUILDING MOUNTED HIGH PRESSURE SODIUM, DARK SKY COMPLIANT WALL PACK FIXTURE	COOPER	Z-PAK CUTOFF - HPFZ/FC/CO15C	1	Sylvania Philips GE	70W CMH	4000	Pulse Start Electronic Ballast	79	
CC	BUILDING MOUNTED COMPACT FLUORESCENT, DARK SKY COMPLIANT WALL PACK FIXTURE	COOPER	LDWP-FC-4A-120	N/A	N/A	LED	4000	Electronic Driver	40	
CCX	BUILDING MOUNTED COMPACT FLUORESCENT, DARK SKY COMPLIANT WALL PACK FIXTURE	COOPER	LDWP-FC-4A-120-EMLED-CD	N/A	N/A	LED	4000	Electronic Driver Emergency Battery Pack	40	Provide with factory LED Emergency Cold Rated Battery Pack

MICHAEL L. ROBERTS
STATE OF WASHINGTON
21901
REGISTERED ARCHITECT

DESIGN WEST
ARCHITECTS, P.A.
7513 W KENNEWICK AVE SUITE D
KENNEWICK, WA. 99336
PH.: (509) 783-2244 FAX (509) 783-8740

© COPYRIGHT DESIGN WEST ARCHITECTS P.A.
ALL DRAWINGS AND WRITTEN MATERIAL APPEARING HEREIN ARE THE PROPERTY OF DESIGN WEST ARCHITECTS P.A. AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION OF ARCHITECT

1/10/2013

HARGIS ENGINEERS | MECHANICAL · ELECTRICAL · TELECOMMUNICATIONS
Hargis Engineers, Inc.
600 Stewart Street, Suite 1000 | Seattle, WA 98101
t | 206.448.3376 f | 206.448.4450 w | hargis.biz

KENNEWICK SCHOOL DISTRICT
1315 BUILDING RENOVATIONS
1315 WEST 4TH AVENUE
KENNEWICK, WA.
99336

REVISIONS

DRAWN BY: JPH, DB
CHECKED BY: MLR
DATE: 12/19/2012
JOB NUMBER: 1278
SHEET NAME: **LIGHTING FIXTURE SCHEDULE**
SHEET: **E0.03**